USPTO Customer No. 25280

Case 9292

## **AMENDMENT**

- 1. (Cancelled)
- 2. (Currently amended) A composite article according to claim 1 comprising a silicone rubber matrix reinforced with polyaramid textile wherein said polyaramid textile is bonded to said silicone rubber by means of a bonding composition comprising an acryloxy organosilane in which said polyaramid is activated with an epoxy compound.
- (Currently amended) A composite article according to claim 1 claim 2 in which the polyaramid is a p-phenylene polyaramid.
- (Currently amended) A composite article according to claim 1 claim 2 in which said bonding composition further comprises an epoxy organosilane.
- (Original) A composite article according to claim 4 in which said bonding composition further comprises a vinyl organosilane.
- (Currently amended) A composite article according to claim 1 claim 2 in which said organosilane is a trimethoxy silane.
- (Currently amended) A composite article according to elaim 1 claim 2 in which said polyaramid textile comprises polyaramid single end or cabled cords.
- 8. (Currently amended) A composite article according to elaim 1 claim 2 in which said polyaramid textile is a weft insertion warp knit fabric having polyaramid weft and/or warp yarns.

USPTO Customer No. 25280

Case 9292

- (Currently amended) A process for manufacturing an <u>a</u> polyaramid reinforced silicone rubber article comprising the steps of:
  - Selecting a polyaramid textile,
  - b) Optionally activating the polyaramid textile with an epoxy compound, and/or optionally activating the polyaramid textile with a plasma,
  - c) Dipping the polyaramid textile into an organosilane dip comprising acryloxy organosilane, and
  - Bonding the dipped polyaramid textile to silicone rubber.
- (Original) A process according to claim 9 wherein said organosilane dip further comprises an epoxy organosilane.
- 11. (Original) A process according to claim 9 wherein said organosilane dip is an aqueous dip.
- 12. (Original) A process according to claim 9 in which epoxy activation is followed by plasma activation, which is, in turn, followed by the organosilane dipping step.
- 13. (Original) A process according to claim 12 in which said plasma activation comprises an air plasma.
- 14. (Original) A process according to claim 13 in which said plasma activation comprises an air plasma further including water as an aerosol.

USPTO Customer No. 25280

Case 9292

15. (Original) A process according to claim 9 in which said organosilane dip further comprises an amino functional organosilane.